


Lötfreie Stift-Kabelschuhe ohne Isolation

nach DIN 46 230



Werkstoff: Cu-HCP (0,1 – 6 mm²) bzw. Cu-ETP (10 – 95 mm²)
Oberfläche: galvanisch verzinkt

Leiter- querschnitt mm²	Bestell-Nr.	Maße in mm							Cu-Gewicht 100 St. ca. kg	Ansetz- geräte
		l ₁	l ₂	a	d ₁	d ₂	b	h		
0,5 – 1	RSQ 5338 – 1	17	10	5	1,6	1,9	–	–	0,07	WZ 43 WZ 100-66 K 25 WZ 20 WZ 1
	RSQ 5338.002 – 1	12	5	5			–	–	0,06	
1,5 – 2,5	RSQ 5338 – 2,5	17	10	5	2,3	1,9	–	–	0,08	
	RSQ 5338.002 – 2,5	22	15	5			–	–	0,09	
4 – 6	RSQ 5338 – 6	20	11	6	3,6	2,7	–	–	0,16	K 5
10	RSQ 5338 – 10	22	12	8	4,5	–	4,3	2,4	0,25	K 5
16	RSQ 5338 – 16	26	13	10	5,8	–	5,5	2,6	0,43	K 6
25	RSQ 5338 – 25	34,1	16	14	7	–	6,9	2,5	0,69	MP 2
35	RSQ 5338 – 35	41	20	16	8,4	–	8,1	3,2	1,19	
50	RSQ 5338 – 50	45,7	21	19	9,5	–	9,5	3,7	1,89	K 5, K 6
70	RSQ 5338 – 70	55	24	24	11,2	–	11,0	4,0	3,01	MP 2
95	RSQ 5338 – 95	55,5	22	24	13,5	–	12,3	5,1	4,25	