



Braided Sleeving - Standard Package Quantity: 1

	Part Number	Color	Nominal Diameter		Nominal Diameter Range		Length per Reel		Std. Ctn. Qty.
			In.	mm	In.	mm	Ft.	m	
PET Material									
	SE12P-TR0	Black	0.12	3.2	0.094 – 0.250	2.4 – 6.4	200	61.0	4
	SE25P-MR0		White	0.25	6.4	0.125 – 0.375	3.2 – 9.5	1000	304.8
	SE25P-MR10								
	SE25P-MR8	Gray					200	61.0	4
	SE25P-TR0	Black	0.38	9.5	0.188 – 0.500	4.8 – 12.7	1000	304.8	2
	SE38P-MR0						200	61.0	4
	SE38P-TR0						100	30.5	4
	SE50P-CR0						500	152.4	2
BEST SELLER	SE50P-DR0								
	SE75P-CR0	Black	0.75	19.1	0.500 – 1.25	12.7 – 31.8	100	30.5	4
BEST SELLER	SE75P-DR0						500	152.4	2
	SE125P-LR0	Black	1.25	31.8	0.750 – 1.50	19.1 – 38.1	50	15.2	4
	SE125P-TR0						Gray	200	61.0
	SE125P-TR8								
	SE150P-TR0	Black	1.50	38.1	1.00 – 2.13	25.4 – 54.0			
	SE175P-TR0			1.75	44.5	1.25 – 2.75	31.8 – 69.9		
Flame Retardant PET Material									
	SE12PFR-MR0	Black	0.12	3.2	0.094 – 0.250	2.4 – 6.4	1000	304.8	2
	SE12PFR-TR0						200	61.0	4
	SE25PFR-MR0	Black	0.25	6.4	0.125 – 0.375	3.2 – 9.5	1000	304.8	2
	SE25PFR-TR0						200	61.0	4
	SE25PFR-TR8	Gray							
	SE38PFR-MR0	Black	0.38	9.5	0.188 – 0.500	4.8 – 12.7	1000	304.8	2
	SE38PFR-TR0						200	61.0	4
	SE50PFR-CR0						100	30.5	
	SE50PFR-DR0						500	152.4	2
BEST SELLER	SE75PFR-CR0	Black	0.75	19.1	0.500 – 1.25	12.7 – 31.8	100	30.5	4
	SE75PFR-DR0						500	152.4	2
	SE125PFR-TR0		1.25	31.8	0.750 – 1.50	19.1 – 38.1	200	61.0	
	SE150PFR-TR0		1.50	38.1	1.00 – 2.13	25.4 – 54.0			



Braided Sleeving (continued) - Standard Package Quantity: 1

	Part Number	Color	Nominal Diameter		Nominal Wall Thickness		Length per Reel		Std. Ctn. Qty.
			In.	mm	In.	mm	Ft.	m	

Pan-Wrap Braided Sleeving (PET)

NEW	SE38PS-TR0	Black	0.375	9.5	0.027	0.7	200	61.0	2
	SE50PS-CLR0		0.50	12.7			150	45.7	
	SE75PS-CR0		0.75	19.1			100	30.5	
	SE100PS-CR0		1.00	25.4					
NEW	SE125PS-CR0		1.25	31.8					
NEW	SE200PS-LR0		2.0	50.8			50	15.2	

Pan-Wrap Braided Sleeving (Flame Retardant PET)

NEW	SE38PSFR-TR0	Black	0.375	9.5	0.027	0.7	200	61.0	2
NEW	SE125PSFR-CR0		1.25	31.8			100	30.5	
NEW	SE200PSFR-LR0		2.0	50.8			50	15.2	

Fray Resistant (PET)

	Part Number	Color	Nominal Diameter		Nominal Diameter Range		Length per Reel		Std. Ctn. Qty.
			In.	mm	In.	mm	Ft.	m	
	SE38PSC-TR0	Black	0.38	9.5	0.19 – 0.63	4.8 – 15.9	200	61.0	4
	SE50PSC-CR0		0.50	12.7	0.25 – 0.75	6.4 – 19.1	100	30.5	
	SE75PSC-CR0		0.75	19.1	0.63 – 1.0	15.9 – 25.4			

Tinned Copper Braided Sleeving

	Part Number	Color	Nominal Diameter		Current Capacity	Length per Roll	
			In.	mm		Ft.	m
NEW	SE12TC-C	Silver	0.125	3.2	25	100	30.5
NEW	SE25TC-C		0.25	6.4	53		
NEW	SE38TC-C		0.375	9.5			
NEW	SE50TC-L		0.50	12.7	62	50	15.2
NEW	SE88TC-L		0.875	22.2	100		
NEW	SE100TC-L		1.0	25.4	120		
NEW	SE125TC-L		1.25	31.8	145		
NEW	SE150TC-L		1.50	38	165		
NEW	SE200TC-L		2.0	50.8	180		